



## CONAP® S-13

CONAP S-13 solvent and thinner is designed for dilution of CONAP® CE-1170 conformal coating for both dip and spray applications. It contains powerful solvents but has a fairly short retention time. CONAP S-13 can also be used for cleanup.

### TYPICAL PRODUCT CHARACTERISTICS

Color	Water White
Specific Gravity @ 25°C	0.85 - 0.88
Flashpoint	80°F (Closed-Cup)
Vapor Density @ 25°C	3.60 – 3.70
Water Content	Less than 0.1%
Threshold Limit Value (TLV)	100 ppm
Shelf Life @ 25°C (from date of manufacture when stored in the original, unopened containers)	18 months

**CAUTION:** CONAP S-13 solvent is a flammable liquid and should not be used in areas where open flames are present. Provide adequate ventilation and avoid breathing vapors or fumes. If skin contact occurs, wash immediately with soap and water.

Toxicity: Moderate by ingestion and inhalation. Slight skin irritant.

### AVAILABILITY

CONAP S-13 is available in quart, gallon, 5-gallon, and 55-gallon containers.

#### CAUTION:

Responsible handling of Cytec Industries Inc. products requires a thorough preview of safety, health, and environmental issues prior to use. Review the Material Safety Data Sheet(s) for the specific Cytec Industries Inc. product(s) and container label information before opening containers. Ensure that employee exposure issues are understood, communicated to all workers, and controls are in place to prevent exposures above Permissible Exposure Limits (P.E.L.'s). Review safety and environmental issues to be certain controls are in place to prevent injury to employees, the community, or the environment, and ensure compliance with all applicable Federal, State, and Local laws and regulations. For assistance in this review process, please call your Cytec Industries Inc. representative or our office noted below.

[www.cytec.com/conap](http://www.cytec.com/conap)

• Email: [custinfo@cytec.com](mailto:custinfo@cytec.com) Worldwide Contact Info: [www.cytec.com/conap](http://www.cytec.com/conap) Tel: 716.372.9650 Fax: 716.372.1594 •