

CONAP® S-8

RoHS COMPLIANT

CONAP S-8 is halogen free based on IEC 61249-2-21

CONAP S-8 solvent and thinner is designed for dilution of CONATHANE® urethane conformal coatings for both dip and spray applications. It contains powerful solvents but has a fairly short retention time.

TYPICAL PRODUCT CHARACTERISTICS

Color	Water White
Specific Gravity @ 25°C	0.90 - 0.92
Flashpoint	Below 50°F (Closed-Cup)
Water Content	Less than 0.1%
Lower Explosive Limit	1.2% Based on Toluene
Threshold Limit Value (TLV)-TWA	100 ppm Based on Toluene
Shelf Life @ 25°C (from date of manufacture when stored in the original, unopened containers)	18 months

CAUTION: CONAP S-8 Solvent is a flammable liquid and should not be used in areas where open flames are present. Provide adequate ventilation - avoid breathing vapors or fumes. If skin contact occurs, wash immediately with soap and water.

Toxicity: Moderate by ingestion and inhalation. Slight skin irritant.

AVAILABILITY

CONAP S-8 is available in quart, gallon, 5-gallon, and 55-gallon containers.

Related Products:

CONATHANE® CE-1155
CONATHANE® CE-1155-35
CONATHANE® CE-1164

CAUTION:

Responsible handling of Cytec Industries Inc. products requires a thorough preview of safety, health, and environmental issues prior to use. Review the Material Safety Data Sheets(s) for the specific Cytec Industries Inc. product(s) and container label information before opening containers. Ensure that employee exposure issues are understood, communicated to all workers, and controls are in place to prevent exposures above Permissible Exposure Limits (P.E.L.'s). Review safety and environmental issues to be certain controls are in place to prevent injury to employees, the community, or the environment, and ensure compliance with all applicable Federal, State, and Local laws and regulations. For assistance in this review process, please call your Cytec Industries Inc. representative or our office noted below.

www.cytec.com/conap

• Email: custinfo@cytec.com Worldwide Contact Info: www.cytec.com/conap Tel: 716.372.9650 Fax: 716.372.1594 •