



LOCTITE[®] Gear, Chain & Cable Lubricant[™]

January 2007

PRODUCT DESCRIPTION

LOCTITE[®] Gear, Chain & Cable Lubricant[™] provides the following product characteristics:

Technology	Solvent based
Chemical Type	Hydrocarbons
Appearance	Light blue, Viscous liquid
Components	One part - requires no mixing
Viscosity	Low
Cure	Not applicable
Application	Lubrication
Specific Benefit	<ul style="list-style-type: none"> • Foaming action permits fast, deep penetration with reduced amount of run off • Protects parts exposed to harmful or corrosive elements - lubricates, protects and prolongs the life of gears, chains, cables and wire rope • Repels dirt, sand and dust leaving the chain clean and minimizing wear on the gear, chain or cable • Formulated with additives that reduce the "throw-off" from centrifugal force - reduces the frequency of repeat applications • Does not contain CFC

LOCTITE[®] Gear, Chain & Cable Lubricant[™] is a clear, oily spray lubricant that protects and prolongs the life of gears, chains and wire rope.

Typical applications include chain-driven equipment - chain, pin, roller and bushing areas. Sprockets, open gears, wire rope, pulleys, snatch blocks, hoists, conveyors, fork lifts, elevators, overhead door drives, mining, construction, earthmoving and material handling equipment.

TYPICAL PROPERTIES

Specific Gravity @ 25 °C 1.0
Flash Point - See MSDS

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a lubricant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

Directions for use

1. **Note:** Do not apply while parts are moving.
2. Shake can well before using. Product sprays best at room temperature.
3. Generously spray gear, chain, cable or wire rope with lubricant and allow 5 to 10 minutes for complete penetration before operation.
4. Cables and ropes should be completely saturated to ensure protection against corrosion.
5. Regular use will aid in achieving longer life and improved performance.

Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties
Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0