



# **TURCO<sup>®</sup> 4460-BK**

## **LOW COMPOSITE VAPOR PRESSURE SOLVENT**

### **DESCRIPTION:**

TURCO 4460-BK is a water-white liquid formulated to replace methyl ethyl ketone and similar solvents that are environmentally unacceptable due to their high composite vapor pressures.

TURCO 4460-BK is ideal for hand-wipe cleaning of metal surfaces prior to painting or bonding and for cleaning bearings, instruments and electronic components.

### **APPLICABLE SPECIFICATIONS:**

TURCO 4460-BK meets the composite vapor pressure requirements prescribed by the South Coast Air Quality Management District, Rule 1124 "Aerospace Assembly and Component Coating Operations" and the Aircraft/Aerospace NESHAP requirement solvents.

### **FEATURES:**

TURCO 4460-BK offers these features:

1. NESHAP compliant
2. Boeing approved under BAC 5750
3. Evaporates rapidly from surfaces
4. Does not leave surface residue after evaporation
5. Non-corrosive to ferrous and nonferrous metals
6. Excellent solvency for oily soils and paint residues
7. Vapor pressure of 41 mm Hg

### **USE INSTRUCTIONS:**

TURCO 4460-BK is used at full strength. Apply to metal surfaces, using clean, absorbent cloths. Remove soil residue with clean cloth. Keep cloth saturated with TURCO 4460-BK. Change cloth frequently for optimum results.

### **DISPOSAL INFORMATION:**

Dispose of cloths and spent solution per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information. Store used cloths in sealed metal containers to avoid possibility of fire due to spontaneous combustion.

**WARNING! Flammable! Harmful if swallowed.**

TURCO 4460-BK contains aromatic petroleum solvent, ethyl acetate, methyl isobutyl ketone and isopropanol. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, boots and apron made from solvent resistant materials should be worn when handling and using this product.

Do not use TURCO 4460-BK near open flames, cutting torches or welding arcs, since material has a Tag Closed Cup flash point of -5°C.

Do not store containers above 50°C or near strong oxidizing agents. Use care in opening drums to avoid spurting of contents.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

**NOTICE:**

*The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.*

Rev. 3/98(Sup. 2/92) FG:00683  
TDB #86-A