




Wondermask W Temporary Solder Mask 2205

Prevent soldering protected areas in a wave soldering process by applying WonderMASK. Designed to apply smoothly, dry quickly, withstand high leadfree process temperatures, and then be removed easily. Also used for masking conformal coating.



Non-flammable water-washable mask

Quick drying waterwashable mask. Quickly and easily removed with inline and batch cleaning systems.

- Water washable
- Non-flammable
- Non-ozone depleting
- Non-corrosive
- Low odor

Product Packaging

2205-8SQ
Wondermask W
8 oz
24 units/case



2205-G
Wondermask W
1 gal
1 units/case



Chemical & Physical Properties

Appearance	Light blue viscous gel
Odor	Alcohol odor
Flash Point	
VOC (EPA)	53 g/l
VOC (CARB)	
Boiling Point	
Density	1.15

Chemical Composition

CHEMICAL NAME	CAS #
1,2,3- Propanetriol	56-81-5
2-Propanol	67-63-0





Potassium Hydroxide	1310-58-3
Sodium salt of polymeric carboxylic acid	13463-67-7
Titanium dioxide	8031-18-3
DIATOMACEOUS EARTH/ATTAPULGITE CLAY	64742-52-5
Petroleum hydrocarbon	

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe

ITW Contamination Control BV
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.